



## Specifications Ledvance LED Waterproof Batten Damp Proof Eco HLO 40W 4400lm - 865 Daylight | 120cm

[View Product](#)

### General Information

|                          |                                |
|--------------------------|--------------------------------|
| SKU                      | 239285                         |
| EAN                      | 4058075301559                  |
| Brand                    | Ledvance                       |
| Manufacturer Name        | ECO HLO DP 40W 865 1200 GR FS1 |
| Any Lamp all-in warranty | 5 Years                        |
| Average Lifetime (h)     | 50000                          |

### Technical Information

|                             |                |
|-----------------------------|----------------|
| Technology                  | LED Integrated |
| Replaces (Watt)             | 2x36           |
| Wattage                     | 40             |
| Voltage (V)                 | 220-240        |
| Dimmable                    | Not Dimmable   |
| Colour of Light             | White          |
| Colour Code                 | 865 Daylight   |
| Colour temperature (Kelvin) | 6500 Daylight  |
| Colour Rendering (Ra)       | 80-89          |
| Light colour options        | Single Color   |
| Luminous Flux (Lumen)       | 4400           |
| Luminous Efficacy (lm/W)    | 110            |

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|                |     |
|----------------|-----|
| Including bulb | Yes |
|----------------|-----|

|        |       |
|--------|-------|
| Length | 120cm |
|--------|-------|

|                       |                       |
|-----------------------|-----------------------|
| Product Type Category | LED Waterproof Batten |
|-----------------------|-----------------------|

## Fixture Information

|                 |         |
|-----------------|---------|
| Mounting Method | Surface |
|-----------------|---------|

|                    |                  |
|--------------------|------------------|
| Fixture Connection | Terminal, 3-pole |
|--------------------|------------------|

|               |                    |
|---------------|--------------------|
| Optical Cover | PC (Polycarbonate) |
|---------------|--------------------|

|           |      |
|-----------|------|
| IP-rating | IP65 |
|-----------|------|

|                        |                 |
|------------------------|-----------------|
| Impact Protection (IK) | IK08 - 5 joules |
|------------------------|-----------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | -30 to +40 |
|-----------------------|------------|

|                       |      |
|-----------------------|------|
| Colour of the Fixture | Grey |
|-----------------------|------|

|                    |      |
|--------------------|------|
| Colour of material | Grey |
|--------------------|------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|        |           |
|--------|-----------|
| Series | DampProof |
|--------|-----------|

## Dimensions

|             |      |
|-------------|------|
| Length (mm) | 1180 |
|-------------|------|

|            |    |
|------------|----|
| Width (mm) | 72 |
|------------|----|

|             |    |
|-------------|----|
| Height (mm) | 61 |
|-------------|----|

## Sensor Information

## Why Any-lamp?

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

