



**Specifications Noxion LED Panel Delta Pro Pronox V2.0 40W 5280lm - 830 Warm White | 120x30cm - UGR <19 - Dali Dimmable - Philips Xitanium Driver**

[View Product](#)

## General Information

|                          |                                                                                            |
|--------------------------|--------------------------------------------------------------------------------------------|
| SKU                      | 239506                                                                                     |
| EAN                      | 8719157015516                                                                              |
| Brand                    | Noxion                                                                                     |
| Manufacturer Name        | NEW Noxion LED Panel Delta Pro UGR<19 Highlum V2.0 Xitanium DALI 40W 5280lm 3000K 300x1200 |
| Any Lamp all-in warranty | 6 Years                                                                                    |
| Average Lifetime (h)     | 70000                                                                                      |
| Series                   | Delta Pro                                                                                  |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x36               |
| Wattage                     | 40                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |

|                          |                        |
|--------------------------|------------------------|
| Luminous Flux (Lumen)    | 5280                   |
| Luminous Efficacy (lm/W) | 120                    |
| IP-rating                | IP20                   |
| Impact Protection (IK)   | IK02 - 0.20 joule      |
| Fixture Connection       | PI [Push-in connector] |
| Driver Included          | Yes                    |
| Power factor             | >0.90                  |
| Product Type Category    | LED Panel              |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | PS (Polystyrene)               |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 32       |

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|