



Specifications Philips LED Downlight Ledinaire DN070B 12W  
1200lm 60D - 840 Cool White | 170mm - Cutout 145mm

[View Product](#)

Cut-out hole diameter - Ø150mm

General Information

|                          |                                          |
|--------------------------|------------------------------------------|
| SKU                      | 246056                                   |
| EAN                      | 8719514354005                            |
| Brand                    | Philips                                  |
| Manufacturer Name        | DN070B LED12/840 12W 220-240V D150 RD EU |
| Any Lamp all-in warranty | 3 Years                                  |
| Average Lifetime (h)     | 50000                                    |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Wattage                     | 12                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Beam Angle (degree)         | 60                |
| Luminous Flux (Lumen)       | 1200              |
| Luminous Efficacy (lm/W)    | 96                |

|                       |                                |
|-----------------------|--------------------------------|
| Power factor          | >0.90                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 145                           |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK03 - 0.35 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Plastic                       |
| Colour of the Fixture  | White                         |
| Colour of material     | Black                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Series                 | DN070B                        |

## Dimensions

|               |      |
|---------------|------|
| Height (mm)   | 82   |
| Diameter (mm) | 170  |
| Shape         | Spot |

## Sensor Information

## Why Any-lamp?

|                                                                                                                                                                                                                                                                   |           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Type of sensor                                                                                                                                                                                                                                                    | No Sensor |
|  Order from the <b>largest lighting specialist</b> in Europe  <b>Customised</b> quotation |           |
|  Up to <b>7 years warranty</b>  <b>Easy</b> return process                                  |           |