



Specifications Philips LED Downlight  
Coreline DN142B Aluminium White  
19.2W 2300lm 60D - 840 Cool White |  
Cutout 200mm - IP20 - UGR<19.2

[View Product](#)

## General Information

|                          |                            |
|--------------------------|----------------------------|
| SKU                      | 248717                     |
| EAN                      | 8720169502918              |
| Brand                    | Philips                    |
| Manufacturer Name        | DN142B 20S/840 PSU-E UGR19 |
| Any Lamp all-in warranty | 5 Years                    |
| Average Lifetime (h)     | 50000                      |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x18              |
| Wattage                     | 19.2              |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |                                |
|--------------------------|--------------------------------|
| Beam Angle (degree)      | 60                             |
| Luminous Flux (Lumen)    | 2300                           |
| Luminous Efficacy (lm/W) | 120                            |
| Power factor             | >0.95                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| EOC8                   | 50291800                      |
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 4-pole] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 105 |
| Diameter (mm) | 216 |

## Why Any-lamp?

## Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation


 Up to **7 years warranty**


**Easy** return process